


Phase Shifter Requirements

Markus Huening
Meeting on SCRF
Protodriver
Feb. 6th, 2004





Conditions

- Beam loading different in each cavity
- Cavities detuned by Microphonics
- Cavities detuned by Lorentz-Force
- Arrival Phase dependend on upstream Fields
- Jitter of injected Beam (energy, phase, charge); coherent and incoherent



Perfect Beam 2σ



Perfect Beam 4σ




Perfect Beam 6.5σ



Injected Beam

article



Charge according to distance
from center and area covered

$$\sigma_t = 9.9 \text{ ps}$$


$$\sigma_e = 60 \text{ keV}$$

Centroid jitter:


8.2 ps (RMS) (half coherent)

70 keV (RMS) (half coherent)


Cavity Fields




Energy Distribution




Energy Spread




Beam Loss




Beam Loss




Acceptance




Phase Shifter




Phase Shifter




Phase Shifter




Attenuator







Attenuator





Attenuator





Forward Power



Forward Power




Energy Jitter




Coefficient: -22.8, \Rightarrow contribution 1.1 MeV (RMS)

Energy Jitter




Coefficient -22.0,
Contribution 1.1 MeV

Energy Jitter




Coefficient 0.13
Contribution 1.0 MeV
(by now the residual
spread is already
imaginary)


Phase Loop Only ?





Phase Loop Only



Phase Loop Only



Phase Loop Only



Phase Loop Only?

- With a lot of tweaking it is certainly possible to run the $b=0.81$ section with a phase loop only,
- Main problem (for me) was individual beam loading – but that's systematic (Feedforward)
- Phase corrections the same as above
- Changing operation conditions becomes harder
(beam current, voltages)

Summary

- Vector sum control of the “TESLA” section possible without phaseshifter
- Requirements for amplitude correction $< +/- 0.8 \text{ dB}$ (reserve in duration of application)
- Requirements for phase correction $< +/- 8^\circ$ (consider reserve)
- Phase control only operation possible in $\beta=0.81$ section
- Operation with 1/3rd of the current not yet included
- Slightly increased power requirements (excluding insertion losses)